



4-PORT ISDN BRI PHYSICAL INTERFACE MODULES (PIMS)

Product Overview

Juniper Networks 4-port ISDN BRI Physical Interface Modules (PIMs) are for use with Juniper Networks J2320, J2350, J4350, and J6350 Services Routers. These PIMs include four physical ports and support ISDN BRI S/T interface types. For ISDN BRI U interface types, a separate part number is available and an external NT-1 is required.

Product Description

Juniper Networks® 4-port ISDN Basic Rate Interface (BRI) Physical Interface Modules (PIM) for the J Series Service Routers provide the physical connection to ISDN network media types receiving incoming packets from the network and transmitting outgoing packets to the network. The 4-port ISDN BRI PIM forwards packets for processing while performing framing and line-speed signaling.

Features and Benefits

Juniper Networks ISDN PIM provides the following benefits:

- High-density form factor allows for increased bandwidth capabilities while making most effective use of the Juniper Networks J Series Services Routers' modular interface slots.
- Highly integrated backup features required to seamlessly re-establish network access in the event of a connectivity failure.
- The bandwidth on demand feature provides the ability to define bandwidth thresholds that need to be met before the initiation of additional ISDN data connections to control associated connectivity costs.
- Complete configuration and management by command-line interface (CLI) or Web user interface.

Features:

- On demand routing
- Bandwidth on demand
- Dial backup
- Dial-on-demand routing (DDR) floating static and dialer watch

Specifications

Dimensions (H x W x D)

- 0.63 x 5.45 x 6.5 in. (1.6 x 13.8 x 16.5 cm)

Interface connector

- 4x RJ-45

Environmental

- Operating temperature: 32° to 104° F (0° to 40° C)
- Storage temperature: -40° to 158° F (-40° to 70° C)
- Relative humidity: 5% to 90% non-condensing

LEDs

PIM LED's indicate port status with the following LED states:

Color	State	Description
Green	On steadily	Online with no alarms or failures
Red	On steadily	Active with a local alarm; router has detected a failure

Standards and Compliance

Agency/Regulatory Compliance

Safety

- CAN/CSA-C22.2 No.60950/UL 60950 Third Edition - Safety of Information Technology Equipment
- EN 60950 (2000) Third edition - Safety of Information Technology Equipment
- IEC 60950 (1999) Third edition - Safety of Information Technology Equipment

EMC (Emissions)

- FCC Part 15 Class B (USA)
- EN 55022 Class B (Europe)
- AS 3548 Class B (Australia)
- VCCI Class B (Japan)
- BSMI Class B (Taiwan)

Immunity

- EN 55024
- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity
- EN-61000-4-11 Voltage Dips and Sags

European Telecommunications Standardization Institute (ETSI)

- ETSI EN-300386-2: Telecommunication Network Equipment Electromagnetic Compatibility Requirements

Telecom

- FCC Part 68/TIA-968
- IC CS-03

ITU Standards Compliance

- Layer 1: ITU-T I.430
- Layer 2: ITU-T Q.920, ITU-T Q.921: LAPD
- Layer 3: ITU-T I.450, ITU-T I.451

ISDN Protocols Supported

- att5e – AT&T switch variant
- etsi – ETSI switch variant
- nil – National ISDN 1 switch variant
- ntdms-100 – Northern Telecom DMS-100
- ntt – NTT Group switch for Japan

Juniper Networks Services and Support

Juniper Networks is the leader in performance-enabling services that are designed to accelerate, extend, and optimize your high-performance network. Our services allow you to maximize operational efficiency while reducing costs and minimizing risk, achieving a faster time to value for your network. Juniper Networks ensures operational excellence by optimizing the network to maintain required levels of performance, reliability, and availability. For more details, please visit juniper.net/us/en/products-services/.

Ordering Information

Model number	Description
JX-4BRI-S-S	4-port ISDN BRI S/T interface card
JX-4BRI-U-S	4-port ISDN BRI U interface card

Junos Operating System Release

The ISDN PIMs are supported in Juniper Networks Junos® operating system 7.3 or higher on the J Series services routers.

About Juniper Networks

Juniper Networks is in the business of network innovation. From devices to data centers, from consumers to cloud providers, Juniper Networks delivers the software, silicon and systems that transform the experience and economics of networking. The company serves customers and partners worldwide. Additional information can be found at juniper.net.

Corporate and Sales Headquarters

Juniper Networks, Inc.
1194 North Mathilda Avenue
Sunnyvale, CA 94089 USA
Phone: 888.JUNIPER (888.586.4737)
or 408.745.2000
Fax: 408.745.2100
juniper.net

APAC Headquarters

Juniper Networks (Hong Kong)
26/F, Cityplaza One
1111 King's Road
Taikoo Shing, Hong Kong
Phone: 852.2332.3636
Fax: 852.2574.7803

EMEA Headquarters

Juniper Networks Ireland
Airside Business Park
Swords, County Dublin, Ireland
Phone: 35.31.8903.600
EMEA Sales: 00800.4586.4737
Fax: 35.31.8903.601

To purchase Juniper Networks solutions, please contact your Juniper Networks representative at 1-866-298-6428 or authorized reseller.

Copyright 2011 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, Junos, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.