



# G.SHDSL PHYSICAL INTERFACE MODULE

### Product Overview

The G.SHDSL Physical Interface Module (PIM) is for use with Juniper Networks SSG Series Secure Services Gateway including the SSG140, SSG320M, SSG350M, SSG520M and SSG550M and the Juniper Networks J Series Service Routers including the J2320, J2350, J4350, J6300 and J6350. This PIM can be configured as two ports of 2-wire or one port of 4-wire mode and supports Annex A and Annex B.

### Product Description

Juniper Networks® G.SHDSL PIM provides the physical connection to G.SHDSL network media types, receiving incoming packets from the network and transmitting outgoing packets to the network. The G.SHDSL PIM forwards packets for processing while performing framing and line-speed signaling.

### Features and Benefits

Table 1: G.SHDSL PIM Features and Benefits

FEATURE	FEATURE DESCRIPTION	BENEFIT
2-wire and 4-wire G.SHDSL support	Same module can be used in 2-wire and 4-wire environments	Provides investment protection when upgrading WAN connectivity
Automatic configuration	Automatically configures the asymmetric digital subscriber line (ADSL) after negotiating with the DSL access multiplexer (DSLAM)	Minimizes configuration and support overhead
Dedicated network processor	Provides additional processing resources	Helps maintain predictable WAN performance by offloading the J Series or SSG Series CPU
Dying gasp support	Notifies the DSLAM, in the event of power loss, that the SSG Series or J Series is about to go offline	Notifies the network upon unplanned power outages

## Specifications

- ATM over G.SHDSL framing
- EOC support for STU-R
- Noise margin support
- IP quality of service (QoS)
- ATM class of service (CoS) (only unspecified bit rate)
- Virtual circuits per PIM (30 max)
- Dying gasp

### Wire Line Rates

- 2-wire line rate: 192 Kbps to 2.312 Mbps
- 4-wire line rate: 384 Kbps to 4.6 Mbps

### Minimum Software Releases

- Juniper Networks Junos® operating system 7.4: The G.SHDSL PIM with 2-wire functionality is supported on J Series routers.
- Junos OS 7.6: G.SHDSL 4-wire functionality is supported on

### J Series routers.

- ScreenOS 6.0: The G.SHDSL PIM with 2-wire and 4-wire functionality is supported on the SSG140 and SSG300 line.
- ScreenOS 6.0r2: The G.SHDSL PIM with 2-wire and 4-wire functionality is supported on the SSG300 line.

### Dimensions and Weight (H x W x D)

- 0.63 x 5.45 x 6.5 in (1.6 x 13.8 x 16.5 cm)

### Environmental

- Operating temperature: 0° to 40° C
- Storage temperature: -40° to 70° C
- Relative humidity: 5% to 90% noncondensing

### Diagnostics

#### Loopbacks

- Local loopback at GS2237
- Remote loopback at GS2237 towards line side

#### Network Alarms

- Loss of signal defect
- Loss of SYNC word

#### Error Counters

- Loss of sync word (LOSW) errors
- Cyclic redundancy check (CRC) errors
- Segment anomaly (SEGA) errors
- ES (error seconds)
- SES (severely error seconds)
- UAS (unavailable seconds)

## LEDs

PIM LEDs indicate port status with the following LED states:

- Green On steadily Online with no alarms or failures
- Red On steadily Active with a local alarm; router has detected a failure

## Management Capabilities

Telnet/Console/JWeb: Remote and local configuration, monitoring, and troubleshooting

## Standards and Compliance

### Safety

- CAN/CSA-C22.2 No. 60950/UL 60950 Third Edition, Safety of Information Technology Equipment
- EN 60950 (2000) Third Edition - Safety of Information Technology Equipment
- IEC 60950 (1999) Third edition - Safety of Information Technology Equipment

### EMC (Emissions)

- FCC Part 15 Class B (USA)
- EN 55022 Class B (Europe)
- AS 3548 Class B (Australia)
- VCCI Class B (Japan)
- BSMI Class B (Taiwan)

### Immunity

- EN 55024
- EN-61000-4-2 ESD
- EN-61000-4-3 Radiated Immunity
- EN-61000-4-4 EFT
- EN-61000-4-5 Surge
- EN-61000-4-6 Low Frequency Common Immunity
- EN-61000-4-11 Voltage Dips and Sags

### European Telecommunications Standardization Institute (ETSI)

- ETSI EN-300386-2: Telecommunication Network Equipment Electromagnetic Compatibility Requirements

### Telecom

- FCC Part 68/TIA-968
- IC CS-03

### E1 Standards

- ITU G.991.2 (G.SHDSL specification)
- ITU G.994.1 (G.hs specification)
- ITU G.997.1 (Physical Layer Management for DSL transceivers)

## Juniper Networks Service and Support

Juniper Networks is the leader in performance-enabling services and support, which are designed to accelerate, extend, and optimize your high-performance network. Our services allow you to bring revenue-generating capabilities online faster so you can realize bigger productivity gains and faster rollouts of new business models and ventures. At the same time, Juniper Networks ensures operational excellence by optimizing your network to maintain required levels of performance, reliability, and availability. For more details, please visit [www.juniper.net/us/en/products-services/](http://www.juniper.net/us/en/products-services/).

## Ordering Information

PART NUMBER	DESCRIPTION
JX-2SHDSL-S	2 Port 2-wire or 1 Port 4-wire G.SDHSL PIM - Spare

## About Juniper Networks

Juniper Networks is in the business of network innovation. From devices to data centers, from consumers to cloud providers, Juniper Networks delivers the software, silicon and systems that transform the experience and economics of networking. The company serves customers and partners worldwide. Additional information can be found at [www.juniper.net](http://www.juniper.net).

---

**Corporate and Sales Headquarters**

Juniper Networks, Inc.  
1194 North Mathilda Avenue  
Sunnyvale, CA 94089 USA  
Phone: 888.JUNIPER (888.586.4737)  
or 408.745.2000  
Fax: 408.745.2100  
www.juniper.net

**APAC Headquarters**

Juniper Networks (Hong Kong)  
26/F, Cityplaza One  
1111 King's Road  
Taikoo Shing, Hong Kong  
Phone: 852.2332.3636  
Fax: 852.2574.7803

**EMEA Headquarters**

Juniper Networks Ireland  
Airside Business Park  
Swords, County Dublin, Ireland  
Phone: 35.31.8903.600  
EMEA Sales: 00800.4586.4737  
Fax: 35.31.8903.601

To purchase Juniper Networks solutions, please contact your Juniper Networks representative at 1-866-298-6428 or authorized reseller.

Copyright 2010 Juniper Networks, Inc. All rights reserved. Juniper Networks, the Juniper Networks logo, Junos, NetScreen, and ScreenOS are registered trademarks of Juniper Networks, Inc. in the United States and other countries. All other trademarks, service marks, registered marks, or registered service marks are the property of their respective owners. Juniper Networks assumes no responsibility for any inaccuracies in this document. Juniper Networks reserves the right to change, modify, transfer, or otherwise revise this publication without notice.